

Specifications Artwork



Only make use of the drawing(s) provided by Intrapec for making up the artwork. The artwork must be placed in the drawing without removing or changing any of the existing data. However, to make sure this data does not end up in the final print, give all non-artwork related data a different spot color and place it in a different layer. Our recommendation is to make use of the EPS-file (not the PDF file) for creating the artwork since all die-cut related data in this file already has a different spot color and is placed in a different layer. The graphic programs *Adobe Illustrator* and *Art Pro* can be used for opening the EPS file and creating the artwork.

	Offset	Flexo	Digital printing
Colors	CMYK, Pantone, PMS kleuren (no combinations or RGB)	Pantone, PMS kleuren (no CMYK or RGB) White in a different layer and as spot color	CMYK (no Pantone, PMS or RGB)
Positioning	Overfill 10 mm (min. 5 mm) Keep essential images 2 mm from cut- and crease lines (unless completely overflowing)	Overfill 10 mm (min. 5 mm) Keep essential images 5 mm from cut- and crease lines (unless completely overflowing)	Overfill 10 mm (min. 5 mm) Keep essential images 2 mm from cut- and crease lines (unless completely overflowing)
Images	Enclose images Flatten transparencies (min10%)	Do not enclose images Do not flatten images (keep layers) EAN height min. 35 mm	Enclose images Flatten transparencies (min10%)
Text	Sans serif and min. 6 pts (1,5mm) Convert text to outlines	Positive: min. 6pt (1,5mm); Negative: min. 8pt (2mm) Convert text to outlines	Sans serif and min. 6 pts (1,5mm) Convert text to outlines
Line width	Min. 0,25 mm	Positive: min. 0,25 mm; Negative: min. 0,35 mm	Min. 0,25 mm
Image resolution	min. 150 dpi (preference 300 dpi)	min. 150 dpi (preference 300 dpi)	min. 150 dpi (preference 300 dpi)
Grid linearity	196 lpi	20 l/cm	196 lpi

Sending Data *Send by mail (<15mb) or upload via WeTransfer (>15mb) citing the order number and/or quote number and/or general description.*

1. *PDF file (HR or Certified) of the CAD drawing containing the artwork*
2. *PDF file (HR or Certified) of only the artwork*

Intrapec only inspects if the received artwork meets above mentioned specifications, and if the right file formats have been send. We do not check the artwork for graphical errors. The person creating the artwork must inspect the artwork closely before sending it. Pay special attention to the following: spelling mistakes, artwork on not visible sides, orientation of text, color changes and overfill.